

HYUNDAI


4AD222C



MARINE

Power Rating

Conditions	Model	Max. Power		rpm	Emission
		kWm	PS		
50Hz	4AD222CA(F)	553	752	1500	IMO Tier II/III EPA Tier 3
60Hz	4AD222CA(S)-II	736	1000	1800	
	4AD222CA(S)	664	903		



* No reduction in rating for intake air temperature is up to 45°C (318K) and sea water temperature is up to 32°C (305K), relative humidity is up to 60%

* All data are based on operation to ISO 3046. Performance tolerance of ±3%

Key Features and Benefit

High Performance

- Advanced fuel injection system with common rail
- Compliance with emission regulation (IMO Tier II/III, EPA Tier 3)
- High-efficiency SCR
- Smoke reduction
- Increased durability of key components

Convenience

- Auto tensioner
- Turning device
- Electrical oil drain pump
- CCV for engine room cleanliness

Economical



- Decreasing fuel consumption to average 5% by downsizing
- Increased oil & filter replacement cycle (250hr → 500hr)

Warranty

- Maximum 3 years warranty provided through extended warranty option

Engine Specifications

Engine Model	4AD222C (DX22)	
Cylinders and Arrangement	12-cylinder / V type	
Bore x Stroke	128 x 142 mm	
Displacement	21.9 liter	
Compression Ratio	17.0 : 1	
Firing Order	1-12-5-8-3-10-6-7-2-11-4-9	
Direction of Revolution	Counterclockwise viewed from Flywheel	
Fuel system	Common rail controlled by ECU	
Starting system	Electric starting by starter motor	
Starter motor capacity	24V - 7.0A	
Alternator capacity	24V - 80Ah	
Battery	24V - 200Ah	
Aspiration	Wet turbocharger & intercooler	
Flywheel Housing	SAE #1 (FW: 14")	
Cooling system	Heat exchanger / Keel Cooling	
Cooling water capacity	Max : 105 liter, Min : 94.5 liter	
Fresh water pump type	Centrifugal (Pulley type)	
Sea water pump type	Rubber Impeller	
After Treatment System	IMO Tier-II / EPA Tier 3 : Not Required IMO Tier-III : SCR	
Lubricant Oil	Oil pan capacity	Max : 69 liter, Min : 36 liter
	Pressure	Full load : 3.0, Idle : 1.0 (kg /cm ²)
Dimension (L x W x H)	1914 x 1323 x 1346 mm	
Dry Weight	2020 kg	



※ Specifications are subject to change without prior notice.

